

# 19" Wall Cabinet (disassembled)



## Key Features :

- Disassembled (Flatpack)
- Single section, 19" standard
- Tempered glass door with +180° turning
- Removable side panels (lock optional)
- Cable entry on top and bottom with knock out plate
- 2 x Fan cut-out on top cover (fans not supplied)
- Mounting profiles front and back



## Specifications :

Material : SPCC cold rolled steel  
 mounting profile : 2 mm  
 other : 1.2 mm

Protection : IP20

Complies with: ANSI/EIA RS-310-D, IEC60297-2  
 DIN41494:part1 & part7  
 UL & ROHS

Capacity : static load 60 kg

Color : Black RAL9004

Depth : 600 mm

Width : 600 mm

## Order Information


Order code :

<b>LWC1906U60F</b>	<b>06U</b>	EAN : 5904014201840
<b>LWC1909U60F</b>	<b>09U</b>	EAN : 5904014201857
<b>LWC1912U60F</b>	<b>12U</b>	EAN : 5904014201673
<b>LWC1915U60F</b>	<b>15U</b>	EAN : 5904014201680
<b>LWC1918U60F</b>	<b>18U</b>	EAN : 5904014201697


**LWCLOCKF**

EAN : 5904014201703


(lock for sidepanel - 1 pc)




Back



Front




Left




Back Front


H : 06U - 368 mm  
 09U - 501 mm  
 12U - 635 mm  
 15U - 769 mm  
 18U - 901 mm



Top



Mounting dimension



Pest & mouse prevention ventilation holes